

CONTROL4 WIRELESS 0-10V DIMMER, CONTEMPORARY



CONTROL4® C4-TV120277-C, C4-TV240-C

Control4's new Contemporary Lighting is designed to elevate lighting control and aesthetics. With a beautiful design that suits the smart home of today, Contemporary Lighting gives you a new industrial design that customers will love.

Experience elegant, in-wall control of the increasingly popular 4-wire 0-10V dimmable fluorescent ballasts and LED lights. Available in 10 stylish colors and finishes. 120V/277V or 240V.

Faceplates are not included—remember to order faceplates separately.

- Capable of sinking or sourcing 100mA for control of up to 50 ballasts
- Built-in relay provides separate on/off control of line-voltage when required
- Continuously measures energy being used by the attached load
- Elegant, sophisticated design makes a beautiful addition to any home or business
- Custom engraving available to clearly identify which light each dimmer controls
- Backlit button engraving with programmable color control for easy readability regardless of time of day or light level
- Programmable RGB LEDs provide status feedback for lighting and other devices in the system
- Ambient light sensor automatically adjusts backlight and status LED brightness depending on the light level in the room
- Available in a wide array of gloss and satin colors (see Available Colors)
- Control4 screw-less faceplates, sold separately, provide a sleek profile (see Available Accessories)

CONTROL4 WIRELESS 0-10V DIMMER, CONTEMPORARY

SPECIFICATIONS

Model number	C4-TV120277-C and C4-TV240-C
Power requirements	C4-TV120277-C: 110-277VAC +/-10%, 50/60 Hz C4-TV240-C: 220VAC-240VAC +/-10%, 50/60 Hz This device requires a neutral AC connection.
Power consumption	120V: 485 mW 240V: 1.0W 277V: 1.18 W
Control communications	Zigbee, IEEE 802.15.4, 2.4 GHz, 15-channel, spread-spectrum

Load types/ratings

Supported load types	Four-wire 0-10V and 1-10V dimmable fluorescent ballasts and LEDs, sink or source
Maximum load (switched hot)	120V: 15A 240V: 10A 277V: 8A
Maximum load (0-10V control)	100mA sink or source

Mechanical and Environmental

Weight	0.5 kg (0.12 lb)
Shipping weight	0.08 kg (0.18 lb)
Wall box volume	94.2 cubic cm (5.75 cubic in.)
Operating temperature	0 to 40 °C (32 to 104 °F)
Storage temperature	-20 to 70 °C (-4 to 158 °F)
Humidity	5% to 95% non-condensing

Available colors

C4-TV120277-C	AU, BI, BL, BR, GR, IV, LA, MB, SW, WH
C4-TV240-C	AU, BI, BL, MB, SW, WH

Available accessories

Faceplate, 1 Gang (C4-FP1-xx)	AU, BI, BL, BR, CH*, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*
Faceplate, 2 Gang (C4-FP2-xx)	AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*
Faceplate, 3 Gang (C4-FP3-xx)	AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*
Faceplate, 4 Gang (C4-FP4-xx)	AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*
Color Kit (C4-CKFPDAPD-xx)	AU, BI, BL, BR, GR, IV, LA, MB, SW, WH
Engraved Button, Rocker (C4-EBDR-xx)	AU, BI, BL, BR, GR, IV, LA, MB, SW, WH

Gloss colors: BL=Black, BR=Brown, GR=Gray, IV=Ivory, LA=Light Almond, WH=White
Satin colors: AU=Aluminum, BI=Biscuit, MB=Midnight Black, SW=Snow White
Metal finishes: CH=Chrome, MS=Matte Stainless, SN=Satin Nickel, VB=Venetian Bronze
*Coming soon

MORE INFO

Find details of the product's Limited Warranty at snapav.com/warranty or request a paper copy from Customer Service at **866.424.4489**.

Find other legal resources, such as regulatory notices and patent information, at snapav.com/legal.

MOST RECENT DATA SHEET REVISION



INSTALLATION GUIDE



INSTALLATION GUIDE

