

KALEIDESCAPE DV700 DISC VAULT



kaleidescape



AT A GLANCE:

- Automatically imports your Blu-ray discs and CDs and catalogs your DVDs
- Loads up to 320 discs making it easy to add great content to your library
- Enables instant playback of content imported from Blu-ray disc
- Supports fully-automated playback of protected DVDs to any Kaleidescape movie player

THE KALEIDESCAPE DV700 DISC VAULT AUTOMATICALLY IMPORTS YOUR BLU-RAY DISCS AND CDS, AND ALLOWS YOU TO PLAY YOUR PROTECTED DVDS WITHOUT TOUCHING A PHYSICAL DISC.

Insert your Blu-ray discs and CDs and the DV700 Disc Vault automatically copies them onto your Kaleidescape System. Protected DVDs are not imported, but are played directly from the disc vault's optical drive to any Kaleidescape movie player. Up to 320 discs can be loaded into the vault making it easy to import or play your collection of movies and music on disc.

Discs in the vault remain organized and easy to find. To retrieve one, simply navigate to the title using the onscreen display of any player, and select Eject Disc.

The presence of a Blu-ray disc in the vault enables instant playback of the copy on the server by any M-Class player in the system. If a Blu-ray disc is ejected, the system cannot play the movie until it is reinserted.

The DV700 Disc Vault connects to your home network with an Ethernet cable, and can be used with Kaleidescape Premiere systems.

KALEIDESCAPE DV700 DISC VAULT



DIMENSIONS

- 17.5in × 8.8in × 21.9in (W × H × D)
(44.5cm × 22.4cm × 55.6cm)

WEIGHT

- 38lbs (17.2kg) empty
- 49lbs (22.2kg) fully loaded with discs

POWER

- Max consumption: 46W
- Typical: 34W
- Standby: 32W
- 100–240V, 50–60Hz universal input

NETWORK

- 100Base-TX/1000Base-T Ethernet (RJ45 connector)

OTHER CONNECTIONS

- USB 2.0 (reserved)
- RS-232 control port (DB-9 male)

ENVIRONMENT

- Operating temperature: 41 to 95°F (5 to 35°C)
- Storage temperature: -4 to 140°F (-20 to 60°C)
- Relative humidity: 20% to 80% non-condensing
- Maximum operating altitude: 10,000ft (3,048m)
- Heat output: 160 BTU/hr (46W) max
- Airflow: 7 CFM (12 m³/hr) max

VENTILATION

- Minimum 1in (2.5cm) space at the front
- Minimum 2in (5cm) space at the rear

RACK MOUNT

- Rack ears included for mounting in a 19in rack, 5U space

CERTIFICATIONS

- CSA 60950-1
- IEC 60950-1
- FCC CLASS B
- CE
- RoHS Compliant

DISC MEDIA

- Blu-ray disc, BD-R, BD-RE
- DVD, DVD-R, DVD-RW, DVD+R, DVD+RW
- CD, CD-R, CD-RW
- Standard 12cm (4.7in) diameter discs

CAPACITY

- 320 discs

REGIONAL PLAYBACK CONTROL

- Each DV700 Disc Vault has a DVD region code which can be changed up to four times.
- A DVD that matches the region code configured for the DV700 Disc Vault can be played by any movie player in the system.

LIMITED WARRANTY

- 3 years

