

Highend speaker

Passive loudspeaker with a unique design and finish

Purifi USHINDI driver with ultra low distortion for crystal-clear sound

Air motion transformer and neodymium magnets for precise and dynamic reproduction

Support of bi-wiring and bi-amping for enhanced flexibility

Aluminium waveguide with magnetic speaker cover for easy removal

Massive aluminium stand with innovative decoupling technology

LOEWE. was found by the Loewe brothers as Radio Frequenz GmbH in Berlin in 1923. Today we still design, develop and produce consumer electronics – Made in Germany.









### Highend speaker



#### Finest aesthetics and craftsmanship.

Introducing our high-end passive speaker, where art meets engineering. Available in a stunning fractal walnut wood front or white matt, this speaker is not just a sound system - it's a statement piece that enhances any space. Elevate your home decor while indulging in extraordinary sound quality.



#### Precision engineering for exceptional sound.

Experience sound like never before with the Purifi USHINDI speaker driver. Featuring Ultra Low Distortion Transducer Technology, this driver virtually eliminates distortion and delivers unparalleled sound clarity. The innovative PURIFI NeutralSurround technology ensures a smooth response, while the PermanentCore design creates a grain-free backdrop for your music, allowing you to hear every detail as the artist intended.



### Dynamic audio performance.

Feel the power of sound with our Air Motion
Transformer (AMT) and robust neodymium magnets.
These advanced technologies deliver precise,
dynamic audio that immerses you in your favorite
music, movies, and games. Prepare to be captivated
by the depth and detail of your audio experience.



### Innovative design for enhanced sound.

The solid aluminum stand incorporates cutting-edge decoupling technology, ensuring that your speaker delivers the purest sound possible. This design not only enhances audio performance but also provides a stylish and stable base for your listening enjoyment.



### Versatile connectivity options.

Unlock your audio system's full potential with our biwiring and bi-amping capabilities. Tailor your setup to suit your listening preferences and achieve enhanced performance with flexible connectivity options that adapt to your unique sound needs.



### Convenient maintenance with style.

Enjoy easy access to your speakers with the magnetic cover that allows for quick removal. This thoughtful design not only simplifies maintenance but also enhances the aesthetic appeal of your speaker, allowing you to showcase the beauty of the craftsmanship underneath.

### Achievements



"Gorgeous in appearance, well thought out down to the last detail and with a sound that is almost overwhelmingly atmospheric and controlled - the grand inicio is a more than promising debut from Loewe."

FIDELITY magazine, March/April 2025, about Loewe grand inicio



"The drivers from Purifi Audio are at the heart of the speakers' sound, while extravagant details on the outside fulfil Loewe's high design ethos."

AUDIO stereoplay magazine, 3/2025, about Loewe grand inicio

## Highend speaker

| Speaker s                    | ize                                       |       |                               |                             |         |
|------------------------------|---|-------|-------------------------------|-----------------------------|---------|
| grand inicio<br>stand speake | r   | [ ]   | inicio<br>shelve speake       | er                          | [ ]     |
| Configura                    | tion                                      |       |                               |                             |         |
| stereo pair                  |   | []    | multi channe<br>(please speci |                             |         |
| Main colo                    | ur  |       |                               |                             |         |
|                              | grand incio:<br>fractal walnut + titanium | []    |                               | incio:<br>walnut + titanium | [ ]     |
|                              |   |       |                               | white + titanium            | []      |
| Speaker c                    | over                                      |       |                               |                             |         |
|                              | black                                     |       |                               |                             |         |
| System co                    | omponents                                 |       |                               |                             |         |
| multi.room ar                | mp  | [ ]   |                               |                             |         |
|                              |   |       |                               |                             |         |
| Loewe multi.roon             | n amp Cr<br>r multiroom and homecinema    | olour |                               | Model                       | Article |
|                              | 200 watts total music power               | black | 0                             | multi.room amp              | 61600   |

Highend speaker

Additional information

## www.loewe.tv



## my Loewe app



## Your Loewe contact

## We are happy to help personally.

Our Loewe Customer Care Center is here for you: Monday to Friday 09:00 – 17:00 o'clock ccc@loewe.de | 0049 9261 99 500

## Your Loewe dealer

### Highend speaker

| Technical data   |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Loewe highend speaker  | grand inicio   | inicio   |  |  |  |  |
| Audio (acoustic)   |  |  |  |  |  |  |
| Frequency range (ca. Hz) @ ±3 dB                                   | 35-22.000  | 45-22.000  |  |  |  |  |
| Max. sound pressure level (ca. dB SPL) @ 1m, pink noise, max. vol. | 89   | 86   |  |  |  |  |
| Max. load capacity   | 400 @ 4Ω   | 200 @ 4Ω   |  |  |  |  |
| Orientation front / side / up / rear firing                        | •/-/-  | •/•/-/-  |  |  |  |  |
| Acoustic speaker concept   | bass reflex  | closed   |  |  |  |  |
| Channel configuration (speaker layout)                             | 2.0 (stereo pair)  | 2.0 (stereo pair)  |  |  |  |  |
| Driver total amount  | 3  | 4  |  |  |  |  |
| Driver active  | 1x AMT, 2x 6,5"  | 1x AMT, 1x 4"  |  |  |  |  |
| Driver passive   | _  | 2x 4"  |  |  |  |  |
| 2-channel crossover  | • @ 2.300 Hz   | • @ 3.500 Hz   |  |  |  |  |
| Connectivity and interfaces  |  |  |  |  |  |  |
| Speaker terminals  | • (stereo)   | • (stereo)   |  |  |  |  |
| Banana plugs   | • (stereo)   | • (stereo)   |  |  |  |  |
| Terminals and plugs gold plated                                    | •  | •  |  |  |  |  |
| Bi-wiring  | 0  | 0  |  |  |  |  |
| Energy and environment   |  |  |  |  |  |  |
| Ambient temperature while in operation                             | 5-40° C  | 5-40° C  |  |  |  |  |
| Relative humidity (non-condensing)                                 | 35-90%   | 35-90%   |  |  |  |  |
| Dimensions   |  |  |  |  |  |  |
| Weight (ca. kg)  | 33,5   | 7,5  |  |  |  |  |
| W* x H x D (ca. cm)  | 26,0 x 135,0 x 30,0                                      | 18,5 x 30,0 x 27,5                                       |  |  |  |  |
| Scope of Delivery  |  |  |  |  |  |  |
| Manual   | •  | •  |  |  |  |  |
| Other cables   | Bridge wire, speaker cable (4 m)                         | Bridge wire, speaker cable (5 m)                         |  |  |  |  |
| Others   | Stand, spikes, leveler, speaker cover                    | Speaker cover  |  |  |  |  |
| Optional accessories   | <u> </u>   |  |  |  |  |  |
| Selection of recommended audio systems                             | multi.room amp   | multi.room amp   |  |  |  |  |
| Specials   | AMT: Air Motion Transformer                              | AMT: Air Motion Transformer                              |  |  |  |  |
|  | Powerful neodymium magnets                               | Powerful neodymium magnets                               |  |  |  |  |
|  | Massive aluminium wave guide                             | Massive aluminium wave guide                             |  |  |  |  |
|  | Large but lightweight and stiff alloy membranes          | Lightweight and stiff alloy membrane                     |  |  |  |  |
|  | Four-layer, copper-plated alloy coil with 39 mm diameter | Four-layer, copper-plated alloy coil with 30 mm diameter |  |  |  |  |
|  | Glass fibre reinforced carrier                           | Glass fibre reinforced carrier                           |  |  |  |  |
|  | Ultralinear positive and negative excursion              | Ultralinear positive and negative excursion              |  |  |  |  |
|  | Neutral speaker bead geometry                            | Neutral speaker bead geometry                            |  |  |  |  |
|  | Ventilated die-cast basket                               | Ventilated die-cast basket                               |  |  |  |  |
|  | Screw sockets for spikes, pucks or base plate            | Screw sockets for spikes, pucks or base plate            |  |  |  |  |

<sup>• =</sup> available, • = optional, — = not available

Technical changes, delivery options, errors and price changes reserved. All product and company names are trademarks™ or registered® trademarks of their respective owners. Their use does not imply any affiliation with or endorsement by these companies. Digital services and content (e.g. apps) and server platforms are provided by third parties. Available for download in the App Store. Observe the terms of use of the third party on the device. The provision, availability (including in certain territories), updating and termination of the provision of this digital content and services on the device are at the sole discretion of the third party.