




# Datasheet: GS-SMT-HOA

## Under Floor Heating controller

Job Name:		Location:	
Purchaser:			
Engineer:			
Submitted To:		For	Reference    Approval    Construction
Submitted By:		Date:	
Unit Designation:	Schedule #:	Model No.:	

### Features:

- 8 x 10K Zone Temperature sensors
- 8 Relay Outputs, 5Amp
- Up to 4 Controllers (total 32 zones) connected with CoolLinkBridge
- Up to 10 Controllers (total 80 zones) connected with CoolMasterNet
- RS485 Modbus interface
- Seamless integration of HVAC indoor units with Home Automation / BMS controllers.
- Modbus interface to Home automation and BMS systems
- Allows full control & monitoring of HVAC indoor unit operation
- Wired version: Simple wiring process between CoolPlug and CoolLinkHUB.



### Power

Power Supply:	24 Vdc
Power Consumption:	0.5A

### Operating Conditions


Surrounding Temperature Limits:	-10° C to +50° C +14 F to +122 F
Humidity (%)	0% to 80%
Dimensions (H x W x D) (inches/mm)	0.75 x 7.8 x 4.72 / 19 x 210 x 120
Weight (lbs/kg)	0.26/0.12
Maximum PBUS wiring length (ft/m)	2600/800

### Communication and connectivity

RS485	2 wire, shielded, polarized, twisted pair 20-24 AWG
-------	---

CoolAutomation products are subject to continuous improvements. CoolAutomation reserves the right to modify product design, specifications and information in this datasheet without notice and without incurring any obligations.

# Detailed drawing:



CoolAutomation products are subject to continuous improvements. CoolAutomation reserves the right to modify product design, specifications and information in this datasheet without notice and without incurring any obligations.